

SEPARATOR FOR BATTERY AND ITS MANUFACTURING METHOD AND BATTERY

Patent number: JP2001307710
Publication date: 2001-11-02
Inventor: YAMAMOTO HIROYUKI; SANO TOYOHICO; HORI SHUJI; TANAKA TOMOFUMI; KIDA TATSUNOBU
Applicant: DAIWA SPINNING CO LTD
Classification:
- international: H01M2/16; H01M10/30
- european:
Application number: JP20000116888 20000418
Priority number(s): JP20000116888 20000418

[Report a data error here](#)

Abstract of JP2001307710

PROBLEM TO BE SOLVED: To provide a battery separator, which has a bonding strength and a hydrophilicity, and which can be highly sulfonated in loose sulfonation processing conditions, and in which a battery capacity is improved without reducing a battery life, and to provide a battery with a battery separator incorporated. **SOLUTION:** A nonwoven fabric, which is composed of at least 5 mass % of a synthetic fiber A made by exposing a polymerized polyethylene using a metallocene catalyst (MPE) on at least a part of a fiber surface and at least 5 mass % of a synthetic fiber B made by exposing a high density polyethylene on at least a part of a fiber surface, is manufactured. A thermal bonding using MPE component is performed entirely and a sulfonation is performed to give it a hydrophilicity to make it a battery separator.

Data supplied from the *esp@cenet* database - Worldwide